








	Endless profile	End cap	Profile cover
			
<b>Dimensions</b>			
<b>Characteristics</b>	<p>SlimLite CS fluorescent lights by Hera are recommended for integrated lighting.</p> <p>Max. weight load = 40 kg per 625 mm</p> <p>Merchandise supports, see Invisible 6 range.</p> <ul style="list-style-type: none"> <li>📄 Drawing no. 286-617 Glass shelf 6 mm To be inserted into the profile.</li> <li>⚠️ Observe the assembly and operating instruction</li> </ul>		Can be fitted to the top or bottom of the Endless profile.
<b>Order number</b>	<p>natural anodised aluminium</p> <p>6350 mm ☉ <b>930-659.05</b></p> <p>lto 250–6350 mm ☉ <b>930-660.05</b></p> <p>Incl. 1 profile cover.</p>	<p>silver</p> <p>☉ <b>981-561.05</b></p> <p>Set of 2 pcs.</p>	<p>plastic semi-transparent</p> <p>6350 mm ☉ <b>930-604.03</b></p> <p>lto 250–6350 mm ☉ <b>930-605.03</b></p>



## Wall fixing bracket



The number of wall fixing brackets depends on the weight load and wall structure. Max. distance 1250 mm. For a heavy weight load, max. distance is 625 mm.

The fixtures and wall must be able to support a traction of min. 1.8 kN (180 kg) per point of fixture. The type of fixtures for the wall screw fittings must be determined by the assembly fitter according to the wall structure.

Max. weight load = 150 kg

ⓘ *Observe the assembly and operating instruction*

silver mat

● **300-565.48**

Incl. fixing set for Endless profile.